



NO	CONTENTS [内容]	
①	BATTERY [電池]	CR1632
②	CONNECTOR [コネクタ]	JST [日本圧着端子製造]
	HOUSING [ハウジング]	SHR-02V-S-B
	TERMINAL [ターミナル]	SSH-003T-P0. 2-H
③	+ LEAD WIRE [＋リード線]	UL 3302 AWG30 RED [UL 3302 AWG30 赤]
④	- LEAD WIRE [－リード線]	UL 3302 AWG30 BLACK [UL 3302 AWG30 黒]
⑤	ADHESIVE TAPE [両面テープ]	3M Y-4920 □10
⑥	COVER [外装被覆]	HEAT SHRINKABLE TUBE: YELLOW [熱収縮チューブ: 黄]

NOTE [注記]

- NOMINAL VOLTAGE: 3V [公称電圧: 3V]
- (): REFERENCE DIMENSION AND ANGLE
[() 寸法、角度は参考値]
- OUTER TUBE DEFORMS
OVER AMBIENT TEMPERATURE 40°C.
[周囲温度が40°Cを過ぎると外装チューブは変形します]

PRODUCT NO.	CR-1632/S5DK	SCALE
		1:1
DRAWING NO.	MM1S3SB	 UNIT: mm