

## ERTJZEP473G R-T Characteristics

(for reference)

$$R_{25} = 47 \text{ kohm } \pm 2\%$$

$$B_{25/50} = 4050 \text{ K } \pm 1\%$$

Temp.			Resistance (kohm)			Temp.			Resistance (kohm)			Temp.			Resistance (kohm)		
T(deg.C)	R min.	R typ.	R max.	T(deg.C)	R min.	R typ.	R max.	T(deg.C)	R min.	R typ.	R max.	T(deg.C)	R min.	R typ.	R max.		
-40	1472	1556	1643	25	46.06	47.00	47.94	90	3.794	3.968	4.149						
-39	1381	1458	1539	26	44.03	44.95	45.87	91	3.672	3.842	4.019						
-38	1295	1367	1442	27	42.10	42.99	43.89	92	3.556	3.721	3.893						
-37	1216	1282	1352	28	40.26	41.13	42.01	93	3.443	3.605	3.772						
-36	1141	1203	1268	29	38.51	39.36	40.22	94	3.334	3.492	3.656						
-35	1072	1129	1189	30	36.84	37.68	38.52	95	3.230	3.384	3.543						
-34	1008	1061	1116	31	35.25	36.07	36.89	96	3.129	3.279	3.435						
-33	947.2	996.5	1048	32	33.74	34.54	35.34	97	3.032	3.179	3.331						
-32	890.8	936.6	984.4	33	32.30	33.08	33.86	98	2.939	3.082	3.230						
-31	838.1	880.7	925.0	34	30.93	31.69	32.45	99	2.849	2.988	3.133						
-30	788.9	828.4	869.6	35	29.63	30.36	31.11	100	2.762	2.898	3.039						
-29	742.8	779.5	817.8	36	28.38	29.10	29.83	101	2.678	2.811	2.949						
-28	699.7	733.8	769.4	37	27.20	27.90	28.60	102	2.598	2.727	2.862						
-27	659.3	691.1	724.1	38	26.07	26.75	27.44	103	2.520	2.647	2.778						
-26	621.5	651.1	681.8	39	24.99	25.65	26.32	104	2.445	2.569	2.698						
-25	586.1	613.6	642.2	40	23.96	24.61	25.26	105	2.373	2.494	2.620						
-24	552.9	578.5	605.1	41	22.98	23.61	24.25	106	2.304	2.421	2.544						
-23	521.7	545.6	570.3	42	22.04	22.66	23.28	107	2.237	2.352	2.471						
-22	492.6	514.8	537.8	43	21.15	21.75	22.35	108	2.172	2.284	2.401						
-21	465.2	485.9	507.3	44	20.30	20.88	21.47	109	2.109	2.219	2.333						
-20	439.5	458.8	478.7	45	19.48	20.05	20.63	110	2.049	2.156	2.268						
-19	415.3	433.3	451.9	46	18.71	19.26	19.82	111	1.990	2.095	2.204						
-18	392.6	409.4	426.7	47	17.97	18.50	19.05	112	1.933	2.036	2.143						
-17	371.3	387.0	403.1	48	17.26	17.78	18.31	113	1.879	1.979	2.083						
-16	351.3	365.9	380.9	49	16.58	17.09	17.61	114	1.826	1.923	2.026						
-15	332.4	346.0	360.1	50	15.94	16.43	16.94	115	1.774	1.870	1.970						
-14	314.7	327.4	340.5	51	15.32	15.80	16.29	116	1.725	1.818	1.916						
-13	298.0	309.8	322.1	52	14.73	15.20	15.68	117	1.677	1.768	1.863						
-12	282.3	293.3	304.7	53	14.16	14.62	15.09	118	1.630	1.719	1.812						
-11	267.5	277.8	288.4	54	13.62	14.07	14.52	119	1.585	1.672	1.763						
-10	253.5	263.2	273.1	55	13.11	13.54	13.98	120	1.541	1.626	1.715						
-9	240.3	249.4	258.6	56	12.61	13.03	13.47	121	1.498	1.582	1.669						
-8	227.9	236.4	245.0	57	12.14	12.55	12.97	122	1.457	1.538	1.624						
-7	216.2	224.1	232.2	58	11.68	12.09	12.50	123	1.417	1.497	1.580						
-6	205.2	212.6	220.1	59	11.25	11.64	12.04	124	1.378	1.456	1.537						
-5	194.8	201.7	208.7	60	10.83	11.21	11.60	125	1.340	1.416	1.496						
-4	185.0	191.4	198.0	61	10.43	10.80	11.18										
-3	175.7	181.7	187.8	62	10.05	10.41	10.78										
-2	166.9	172.5	178.3	63	9.686	10.04	10.40										
-1	158.6	163.9	169.2	64	9.334	9.676	10.03										
0	150.7	155.7	160.7	65	8.997	9.331	9.672										
1	143.3	147.9	152.6	66	8.674	8.999	9.332										
2	136.3	140.6	145.0	67	8.364	8.680	9.005										
3	129.7	133.7	137.8	68	8.067	8.374	8.690										
4	123.4	127.2	131.0	69	7.781	8.081	8.389										
5	117.4	121.0	124.6	70	7.507	7.799	8.099										
6	111.8	115.1	118.5	71	7.244	7.528	7.820										
7	106.5	109.6	112.7	72	6.991	7.268	7.553										
8	101.4	104.3	107.2	73	6.748	7.018	7.296										
9	96.60	99.31	102.1	74	6.515	6.777	7.048										
10	92.06	94.60	97.17	75	6.290	6.546	6.810										
11	87.75	90.13	92.53	76	6.075	6.324	6.582										
12	83.67	85.89	88.14	77	5.868	6.111	6.362										
13	79.79	81.87	83.98	78	5.669	5.906	6.150										
14	76.12	78.07	80.03	79	5.477	5.708	5.946										
15	72.63	74.45	76.29	80	5.293	5.518	5.750										
16	69.32	71.02	72.74	81	5.116	5.335	5.562										
17	66.17	67.77	69.38	82	4.946	5.160	5.380										
18	63.19	64.68	66.19	83	4.782	4.990	5.206										
19	60.35	61.75	63.16	84	4.624	4.827	5.037										
20	57.66	58.97	60.28	85	4.473	4.671	4.875										
21	55.10	56.32	57.56	86	4.327	4.519	4.719										
22	52.67	53.81	54.96	87	4.186	4.374	4.568										
23	50.35	51.43	52.50	88	4.050	4.233	4.423										
24	48.15	49.16	50.16	89	3.919	4.098	4.283										
25	46.06	47.00	47.94	90	3.794	3.968	4.149										