

製品品番	静電容量 μF (※)	寸 法					表 示 STYLE	加 工 TYPE
		L	T	H	S	d		
ECQE4103 () FB	0.01 (103)	10.3	4.3	7.4	7.5	0.6	1	D
" 4123 () FB	0.012 (123)	"	4.4	7.5	"	"	"	"
" 4153 () FB	0.015 (153)	"	"	"	"	"	"	"
" 4183 () FB	0.018 (183)	"	"	"	"	"	"	"
" 4223 () FB	0.022 (223)	"	4.8	7.9	"	"	"	"
" 4273 () FB	0.027 (273)	"	5.5	8.0	"	"	"	"
" 4333 () FB	0.033 (333)	"	6.0	9.0	"	"	"	"
" 4393 () FB	0.039 (393)	12.0	4.9	8.0	10.0	"	"	"
" 4473 () FB	0.047 (473)	"	5.0	8.3	"	"	"	"
" 4563 () FB	0.056 (563)	"	"	10.0	"	"	"	"
" 4683 () FB	0.068 (683)	"	5.4	10.5	"	"	"	"
" 4823 () FB	0.082 (823)	"	5.8	11.0	"	"	"	"
" 4104 () FB	0.1 (104)	"	6.3	12.0	"	"	"	"
" 4124 () FB	0.12 (124)	18.5	5.0	10.0	"	"	2	B
" 4154 () FB	0.15 (154)	"	"	12.4	"	"	"	"
" 4184 () FB	0.18 (184)	"	5.4	12.5	"	"	"	"
" 4224 () FB	0.22 (224)	"	5.9	13.0	"	"	"	"
" 4274 () FB	0.27 (274)	"	6.5	14.3	"	0.8	"	"
" 4334 () FB	0.33 (334)	"	7.0	14.9	"	"	"	"
" 4394 () FB	0.39 (394)	"	7.5	15.4	"	"	"	"
" 4474 () FB	0.47 (474)	"	7.8	17.0	"	"	"	"
" 4564 () FB	0.56 (564)	26.0	6.5	16.0	15.0	"	"	"
" 4684 () FB	0.68 (684)	"	7.0	16.5	"	"	"	"
" 4824 () FB	0.82 (824)	"	7.9	17.3	"	"	"	"
" 4105 () FB	1.0 (105)	"	8.5	18.0	"	"	"	"
" 4125 () FB	1.2 (125)	"	9.5	18.9	"	"	"	"
" 4155 () FB	1.5 (155)	31.0	"	19.0	22.5	"	"	"
" 4185 () FB	1.8 (185)	"	11.0	20.5	"	"	"	"
" 4225 () FB	2.2 (225)	"	"	22.0	"	"	"	"

静電容量許容差 (J or K)

品番呼称方法

ECQE 4 103 K F B (400VDC, 0.01μF, ±10%)

標準リード加工品
リード線一方向型、小形化タイプ
静電容量許容差記号 (J=±5%, K=±10%)
静電容量 (※) 参照
定格電圧 (400VDC)

表示例

STYLE 1

103K
400


製造番号

STYLE 2



① 105K
400

製造番号

TYPE D



TYPE B



参 考

品名	汎用巻回メタライズドコンデンサ			
	ECQE (F)			
製品品番	ECQE4*** () FB			
制定日	1986年 6月 4日	設計者	管理責任者	制定者
図名	製品図	設計者	管理責任者	制定者
図番	48B299			