

製品品番	静電容量 μF (※)	寸 法						表 示 STYLE	加 工 TYPE
		L	T	H	S	d			
ECQE6103 () TB	0.01 (103)	12.5	4.5	7.5	10.0	0.6		1	D
" 6123 () TB	0.012 (123)	"	"	7.8	"	"	"	"	"
" 6153 () TB	0.015 (153)	"	5.0	8.2	"	"	"	"	"
" 6183 () TB	0.018 (183)	"	4.9	10.0	"	"	"	"	"
" 6223 () TB	0.022 (223)	"	5.3	10.5	"	"	"	"	"
" 6273 () TB	0.027 (273)	"	5.5	10.9	"	"	"	"	"
" 6333 () TB	0.033 (333)	"	6.0	11.9	"	"	"	"	"
" 6393 () TB	0.039 (393)	"	"	13.4	"	"	"	"	"
" 6473 () TB	0.047 (473)	"	6.5	13.5	"	"	"	"	"
" 6563 () TB	0.056 (563)	19.0	5.4	10.5	"	"	2	B	
" 6683 () TB	0.068 (683)	"	5.8	11.0	"	"	"	"	"
" 6823 () TB	0.082 (823)	"	6.5	12.0	"	"	"	"	"
" 6104 () TB	0.1 (104)	"	6.3	14.0	"	"	"	"	"
" 6124 () TB	0.12 (124)	"	"	14.5	"	0.8	"	"	"
" 6154 () TB	0.15 (154)	"	7.5	15.4	"	"	"	"	"
" 6184 () TB	0.18 (184)	"	8.0	16.0	"	"	"	"	"
" 6224 () TB	0.22 (224)	"	9.0	16.5	"	"	"	"	"
" 6274 () TB	0.27 (274)	26.5	7.0	"	15.0	"	"	"	"
" 6334 () TB	0.33 (334)	"	7.8	17.0	"	"	"	"	"
" 6394 () TB	0.39 (394)	"	8.5	17.9	"	"	"	"	"
" 6474 () TB	0.47 (474)	"	9.3	18.5	"	"	"	"	"
" 6564 () TB	0.56 (564)	"	10.0	20.0	"	"	"	"	"
" 6684 () TB	0.68 (684)	"	11.5	21.0	"	"	"	"	"
" 6824 () TB	0.82 (824)	31.5	11.3	20.5	22.5	"	"	"	"
" 6105 () TB	1.0 (105)	"	12.5	21.9	"	"	"	"	"
" 6125 () TB	1.2 (125)	"	13.5	23.0	"	"	"	"	"
" 6155 () TB	1.5 (155)	"	15.3	24.7	"	"	"	"	"
" 6185 () TB	1.8 (185)	"	16.8	27.0	"	"	"	"	"
" 6225 () TB	2.2 (225)	"	19.5	29.0	"	"	"	"	"

静電容量許容差 (J or K)


品番呼称方法

ECQE 6 103 K T B (630VDC, 0.01μF, ±10%)


標準リード加工品
リード線一方向型
静電容量許容差記号 (J=±5%, K=±10%)
静電容量 (※) 参照
定格電圧 (630VDC)

表示例


STYLE 1





STYLE 2



TYPE D



TYPE B



参 考

品 名	汎用巻回メタライズドコンデンサ			
	ECQE (T)			
製品 品番	ECQE6*** () TB			
制定日	1999年 9月10日	設計者	管理責任者	制 定 者
図 名	製 品 図	図 号	図 番	
	E8Q190			