
| ITEM CODE | CAPACITANCE | | DIMENSIONS | | | | | VOLUME | MARKING | NOTE |
|---------------|-------------|-------|------------|-------|-------|------|-----|---------|---------|------|
| | μF | (*) | L | Т | Н | F | d | (mm³) | STYLE | NOTE |
| ECWF2105 () A | 1. 0 | (105) | 18. 1 | 8. 5 | 13.3 | 15.0 | 0.8 | 1684 | 1 | |
| " 2125 () A | 1. 2 | (125) | 18.8 | 9. 5 | 14.6 | " | " | 2125 | 2 | * |
| " 2155 () A | 1. 5 | (155) | " | 10.5 | 15. 6 | " | " | 2497 | " | * |
| " 2185 () A | 1. 8 | (185) | " | 11. 4 | 16.5 | " | " | 2863 | " | * |
| " 2225 () A | 2. 2 | (225) | " | 12.6 | 17. 6 | " | " | 3 3 4 4 | 11 | * |
| " 2275 () A | 2. 7 | (275) | 23.8 | 11. 4 | 17. 2 | 20.0 | " | 3824 | 11 | * |
| " 2335 () A | 3. 3 | (335) | " | 12.5 | 18.3 | 11 | 11 | 4 4 5 2 | 11 | * |
| " 2395 () A | 3. 9 | (395) | " | 13.5 | 19. 3 | 11 | 11 | 5070 | 11 | * |
| " 2475 () A | 4. 7 | (475) | " | 14.8 | 20.6 | 11 | " | 5882 | " | * |
| " 2565 () A | 5. 6 | (565) | " | 16. 2 | 21.9 | 11 | " | 6784 | 11 | * |
| " 2685 () A | 6.8 | (685) | " | 17. 8 | 23.5 | " | " | 7971 | " | * |


ALTERATION ISSUE DESCRIPTION DATE Company name changed Apr. 2012 Company name changed Apr. 2013 Company name changed Apr. 2015 Company name changed Apr. 2022 SPECIFICATIONS No.

Note

% The specimen (the volume is more than 1750mm³) shall be satisfied with IEC60384-1 Inflammability Category B based on IEC60065. 1998 \sim

ITEM CODE NUMBER STRUCTURE





CONSTRUCTION

The capacitor is of non-inductive construction, wound with metallized polypropylene film dielectric.

The capacitor is enclosed in non-combustible epoxy resin and has two leads.

MARKING

Marking comprises capacitance, capacitance tolerance, rated voltage, type name "WFA" and manufacturer's date code.

PROPERTIES

Capacitance : See table at 1kHz
Capacitance tolerance : ±3%(H). ±5%(J)

Rated voltage : 250VDC

Withstand voltage : 250VDC×150% for 60s

Insulation resistance : $\geq 3000 \text{M}\Omega \cdot \mu \text{F}$ at 100VDC, 20°C for 60s


Dissipation factor : \leq 0.1% at 1kHz, 20°C Category temperature range : From -40°C to +105°C

(including temperature rise on unit surface)

MARKING EXAMPLE



·F: regulation of the root



Film Capacitor Business Unit Device Solutions Business Division Panasonic Industry Co., Ltd.