

Notification about the transfer of the semiconductor business

The semiconductor business of Panasonic Corporation was transferred on September 1, 2020 to Nuvoton Technology Corporation (hereinafter referred to as "Nuvoton"). Accordingly, Panasonic Semiconductor Solutions Co., Ltd. became under the umbrella of the Nuvoton Group, with the new name of Nuvoton Technology Corporation Japan (hereinafter referred to as "NTCJ").

In accordance with this transfer, semiconductor products will be handled as NTCJ-made products after September 1, 2020. However, such products will be continuously sold through Panasonic Corporation.

Publisher of this Document is NTCJ.

If you would find description "Panasonic" or "Panasonic semiconductor solutions", please replace it with NTCJ.

※ Except below description page

"Request for your special attention and precautions in using the technical information and semiconductors described in this book"

Nuvoton Technology Corporation Japan

MN103L08 Series

32-bit Single-chip Microcontroller

■ Overview

The MN103LF08K of 32-bit single-chip microcomputers incorporate multiple types of peripheral functions. This chip series is well suited for camera, TV, VCR, AV, printer, telephone, FAX machine, air-conditioner, music instrument and other applications.

This LSI has flexible and optimized hardware configurations and simple efficient instruction set. This LSI incorporates an internal ROM of 256 KB (maximum) and RAM of 20 KB (maximum), 10 external interrupts, 71 internal interrupts including NMI, 23 timer counters, 8 sets of serial interfaces, A/D converter, 2 sets of watchdog timer, DMA, Buzzer, remote control reception and HDMI-CEC.

With 5 oscillation systems (external high frequency: 4 MHz to 20 MHz/ external low frequency: 32.768 kHz/ internal high frequency: 20 MHz/ internal low frequency: 35 kHz/ PLL: frequency multiplier of high or low frequency) contained on the chip, and the internal clock can be switched to four oscillation clock except the internal low oscillation. The internal clock is generated by dividing the oscillation clock or PLL clock. The best operation clock for the system can be selected by switching its frequency ratio by programming.

A machine cycle (minimum instruction execution time) is 25 ns (internal operating condition: 1.8 V, 40 MHz).

■ Product Summary

This datasheet describes the following model.

Model	ROM Size	RAM Size	Classification	Package
MN103LF08K	256 KB	20 KB *1	Flash EEPROM version	LQFP100-P-1414 QFP100-P-1818B

Note) *1: use On-Chip-Debugger 19.5 KB

■ Features (continued)

• Internal operation clock (continued)

Low-speed oscillation clock (clkx)
Frequency : 32.768 kHz (Max)

• Bus interface

Bus area : 2 MB × 2 banks
Data bus : 8/ 16 bits

• DMA Controller

Transfer area : Internal ROM space / Internal RAM space / Internal I/O area / External memory space
↔ Internal ROM space / Internal RAM space / Internal I/O area / External memory space
Channel : 4 ch
Transfer form : 2 bus cycles transfer
Transfer requests : 44 types
External interrupts:4, Timer:19, Serial:15, IIC: 3, A/D converter:1, Remote control:1, Software:1
Transfer modes : 3 modes (One word transfer / Burst transfer / Intermittent transfer)

• Interrupt functions

Internal interrupts : 71 factors
(Timer:29, Serial I/F:10, IIC:6, Watchdog timer:1, DMA:12, A/D converter:1, Real-time clock: 2,
Remote control: 4, Power Voltage Detection: 2, HDMI-CEC:1, AC zero cross: 2, System error:1)
External interrupts : 10 factor
(IRQn (n = 0 to 7) : 8, NMIRQ (shares an interrupt factor with IRQ7) : 1, KEY: 1)

• Watchdog Timer

Watchdog Timer

On detection of error, hard reset is done inside the LSI
(Non-maskable interrupt is generated by the first watchdog time-out event, and hard-reset is done by a series of two time-out events)
Time-out cycle : CPU clock cycle × N (N = 2¹⁶, 2¹⁸, 2²⁰, 2²⁷)

Watchdog Timer2

On detection of error, hard reset is done inside the LSI
(Non-maskable interrupt is generated by the first watchdog time-out event, and hard-reset is done by a series of two time-out events)
Time-out cycle : Internal low-speed oscillation clock cycle × N (N = 2⁴, 2⁵, 2⁶, 2⁷, 2⁸, 2⁹, 2¹⁰, 2¹¹, 2¹², 2¹³, 2¹⁴, 2¹⁵)

• Timer counter 23 units

General purpose 8-bit timer × 6 unit
8-bit free-run timer × 1 unit
General purpose 16-bit timer × 7 unit
Motor control timer × 1 unit
Baud rate 8-bit timer × 8 unit

Timer 0 (8-bit timer)

Timer count (Up count), external event count, timer pulse output,
PWM output (Cycle is fixed), compare register with double buffer
Clock source : clksp, clksp/4, clksp/16, clksp/32, clksp/64, clksp/128, clkbus/2, clkbus/4, clkbus/8, clkx, external clock

Timer 1 (8-bit timer)

Timer count (Up count), external event count, timer pulse output,
16-bit cascade connection (to timer 0), compare register with double buffer
Clock source : clksp, clksp/4, clksp/16, clksp/32, clksp/64, clksp/128, clkbus/2, clkbus/4, clkbus/8, clkx, external clock

■ Features (continued)

• Timer counter (continued)

Timer 2 (8-bit timer)

Timer count (Up count), external event count, timer pulse output,
 PWM output (Cycle is fixed), 24-bit cascade connection (to timer 0, timer 1), compare register with double buffer
 Clock source : clksp, clksp/4, clksp/16, clksp/32, clksp/64, clksp/128, clkbus/2, clkbus/4, clkbus/8, clkx, external clock

Timer 3 (8-bit timer)

Timer count (Up count), external event count, timer pulse output,
 16-bit cascade connection (to timer 2), 32-bit cascade connection (to timer 0, timer 1, timer 2), compare register with double buffer
 Clock source : clksp, clksp/4, clksp/16, clksp/32, clksp/64, clksp/128, clkbus/2, clkbus/4, clkbus/8, clkx, external clock

Timer 4 (8-bit timer)

Timer count (Up count), external event count, timer pulse output, PWM output (Cycle is fixed)
 Clock source : clksp, clksp/4, clksp/16, clksp/32, clksp/64, clksp/128, clkbus/2, clkbus/4, clkbus/8, clkx, external clock

Timer 5 (8-bit timer)

Timer count (Up count), external event count, timer pulse output, 16-bit cascade connection (to timer 4),
 Clock source : clksp, clksp/4, clksp/16, clksp/32, clksp/64, clksp/128, clkbus/2, clkbus/4, clkbus/8, clkx, external clock

Timer 6 (8-bit free-running timer)

Clock source : clksp, clkbus, clkx, clksp/2¹², clksp/2¹³, clkx/2¹², clkx/2¹³

Timer 7 (16-bit timer)

Timer count (Up count), external event count, timer pulse output,
 PWM output (cycle/duty continuous changeable), input capture (1 system)
 Clock source : clksp, clkbus, external clock, timer 5 output, timer 6 compare match cycle divided by 1, 2, 4, 16

Timer 8 (16-bit timer)

Timer count (Up count), external event count, timer pulse output,
 PWM output (cycle/duty continuous changeable), input capture (1 system)
 32-bit cascade connection (to 16-bit timer 7), 32-bit PWM output
 Clock source : clksp, clkbus, external clock, timer 5 output, timer 6 compare match cycle divided by 1, 2, 4, 16

Timer 9, 10, 11, 12, 13 (16-bit timer)

Timer count (Up count, Down count), external event count, timer pulse output,
 PWM output (cycle/duty continuous changeable), input capture (2 systems)
 Clock source : clkbus, clkbus/8, timer 0, 1 compare match cycle, external clock

Timer M (Motor control 16-bit timer)

Timer pulse output, external event count, complementary 3 phases PWM output (triangular wave and saw-tooth wave output, dead time insertion), 4 phases PWM output (triangular wave and saw-tooth wave output, dead time insertion), output control by external interrupt (Hi-Z output or output data is fixed)
 Clock source : clksp, clkbus, external clock divided by 1, 2, 4, 16

Timer B0, B1, B2, B3, B4 (Baud rate 8-bit timer)

Baud rate timer for serial transfer base clock generation
 Clock source : clksp, clksp/2, clksp/4, clksp/8, clksp/16, clksp/32, clksp/64, clksp/128, clksp/256, clkbus, clkbus/2, clkbus/4, clkbus/8, clkbus/16, clkbus/32, clkbus/64

Timer B5, B6, B7 (Baud rate 8-bit timer)

Baud rate timer for IIC transfer base clock generation
 Clock source : clkx, clksp

■ Features (continued)

- Real time clock

Calendar function (second, minute, hour, month, year)

Alarm function, Cycle interrupt

Clock source : clksp, clkx

- Buzzer

Output frequency : $\text{clksp}/2^9$, $\text{clksp}/2^{10}$, $\text{clksp}/2^{11}$, $\text{clksp}/2^{12}$, $\text{clksp}/2^{13}$, $\text{clksp}/2^{14}$, $\text{clkx}/2^3$, $\text{clkx}/2^4$

- Serial interface 8 channels

UART/ clock synchronous : 5 channels

IIC : 3 channels

Serial 0, 1, 2, 3, 4 (UART/Synchronous serial interface)

UART

Parity check, overrun error/framing error detection

Transfer size can be selected from 7 to 8 bits.

Clock Synchronous

The communication type can be selected from 2-wire or 3-wire.

First transfer bit can be selected from MSB or LSB

Arbitrary size of 2 to 8 bits are selectable.

Continuous transmission, continuous reception, continuous transmission/reception are available.

Synchronous edge selection of transfer clock.

Maximum transfer rate : 5 MHz

Clock source : Baud rate timer Bn output (n = 0 to 4), external clock

Serial 5, 6, 7 (Multi master IIC)

Multi master IIC

100 kHz/ 400 kHz communication is supported

7-bit, 10-bit slave address is settable

General call communication mode is supported

Clock source : Baud rate timer Bn output (n = 5 to 7), external clock

- HDMI-CEC

HDMI-CEC HDMI Specification Compatible with CEC communication option

Clock source : clkx, clkbus

- Remote control reception circuit: 1 unit

Association for Electric Home Appliances format

Clock source : clkx, clkoscesel

- A/D converter Resolution: 10 bit

Channel : 16 channels

Clock source : $\text{clkbus}/2$, $\text{clkbus}/4$, $\text{clkbus}/8$, $\text{clkbus}/16$, $\text{clkx} \times 2$

- Auto reset

Auto reset function can be selected ON/OFF

- Power supply voltage detection circuit

Detection voltage can be set 2.2 V to 4.0 V by software

- Clock monitoring function

Frequency error detection of external / PLL clock.

Hardware reset or non-maskable interrupt generation can be selected by program when a frequency error is detected.

- LED driver: 8 sets

■ Features (continued)

• Port function

I/O ports:	87 pins
CMOS I/O	56 pins
Combination CMOS I/O and oscillation pin:	4 pins
Combination CMOS I/O and Analog input:	16 pins
Combination CMOS I/O and LED driver:	8 pins
Nch open drain I/O:	3 pins
Special function pin	6 pins
Reset input pin (NRST):	1 pin (soft reset is available)
A/D converter reference voltage input pin (VREFH):	1 pin
Capacity connect pin (VOUT18):	1 pin
Function control pins (MMOD, NOCDMOD, ATRST):	3 pins
Power pins	7 pins
power supply pin(VDD50_1,VDD50_2)	3 pins
GND pins (VSS)	4 pins
Power supply separation	
Pins driven by VDD50_1	68 pins (I/O ports: 62 pins)
Pins driven by VDD50_2	25 pins (I/O ports: 25 pins)

• Power supply voltage

VDD50_1	: 2.2 V to 5.5 V
VDD50_2	: VDD50_1 to 5.5 V


• Operating temperature

−40°C to + 85°C

• Package

QFP100pin (QFP100-P-1818B)
LQFP100pin (LQFP100-P-1414)

Pin Description



Request for your special attention and precautions in using the technical information and semiconductors described in this book

- (1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.
- (2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products. No license is granted in and to any intellectual property right or other right owned by Panasonic Corporation, Nuvoton Technology Corporation Japan or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information de-scribed in this book.
- (3) The products described in this book are intended to be used for general applications (such as office equipment, communications equipment, measuring instruments and household appliances), or for specific applications as expressly stated in this book.
Please consult with our sales staff in advance for information on the following applications, moreover please exchange documents separately on terms of use etc.: Special applications (such as for in-vehicle equipment, airplanes, aerospace, automotive equipment, traffic signaling equipment, combustion equipment, medical equipment and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
Unless exchanging documents on terms of use etc. in advance, it is to be understood that our company shall not be held responsible for any damage incurred as a result of or in connection with your using the products described in this book for any special application.
- (4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. We do not guarantee quality for disassembled products or the product re-mounted after removing from the mounting board.
When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.
- (7) When reselling products described in this book to other companies without our permission and receiving any claim of request from the resale destination, please understand that customers will bear the burden.
- (8) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of our company.