

Notification about the transfer of the semiconductor business

The semiconductor business of Panasonic Corporation was transferred on September 1, 2020 to Nuvoton Technology Corporation (hereinafter referred to as "Nuvoton"). Accordingly, Panasonic Semiconductor Solutions Co., Ltd. became under the umbrella of the Nuvoton Group, with the new name of Nuvoton Technology Corporation Japan (hereinafter referred to as "NTCJ").

In accordance with this transfer, semiconductor products will be handled as NTCJ-made products after September 1, 2020. However, such products will be continuously sold through Panasonic Corporation.

Publisher of this Document is NTCJ.

If you would find description "Panasonic" or "Panasonic semiconductor solutions", please replace it with NTCJ.

※ Except below description page

"Request for your special attention and precautions in using the technical information and semiconductors described in this book"

Nuvoton Technology Corporation Japan

1. Mounting method with solder

1-1 Recommended reflow soldering condition


In reflow soldering process, exact temperature-cycle management is essential.

We recommend pre-heating before soldering, so that you can prevent not only package damages or stains but also damages on a printed circuit board, and your process becomes stable.

The following shows our recommended reflow temperature profile.

No	Symbol	Contents	Value
1	T1	Pre-Heating Temperature	150 °C to 200 °C (No Time Regulation)
2	a	Average Ramp-Up Rate	2 °C/s to 3 °C/s
3	Tp	Peak Temperature	max. 260 °C
4	tp	Duration at Peak Temperature	10 s or below
5	tw	Time above Liquid	30 s to 40 s (over 230 °C)
6	b-c	Average Ramp-Down Rate	1.5 °C/s or below
7	T2	Unload Temperature	100 °C
8	-	The Number of Reflow Soldering Repetition	up to 2 times

Above-mentioned temperature is package surface temperature.



1-2 Soldering iron

You can solder manually with small type of soldering irons, but it would cause to shift the soldering position or to damage a package. We recommend that this soldering method be only for repair or experiment.

The following cautions are required in soldering iron use.

- 1) Soldering iron 350 °C Within 3 s

- 2) To fix package please use flux and a solder iron with the diameter $\Phi 0.5$ mm which has a sharp edge.
 (Please note that excessive flux causes low workability.)

- 3) Since strong press causes lead form distortion and solderability degradation, if package pressing is necessary it should be not over 5 N.

- 4) Please use a soldering iron with earth.

- 5) Please solder at low temperature in a short time.

- 6) Mounting by soldering iron can not be applied to leadless packages.
 Please use hot-air soldering iron for repair.

2. Precautions for mounting

When you assemble or mount discrete devices, the following cautions should be kept in mind because of their structural design and mounting operation.

Explaining below is about mechanical shock, soldering, cleaning and using chemicals which need attention in designing and mounting.

In order not to damage electrical characteristics and reliability, the following cautions are required.

2-1 Mechanical shock

Do not apply excessive force to the body. That may become the cause of the distortion of electrical terminal and have a bad influence on mounting. And there is a risk of leading to short circuit, breaking of wire, and damages of package. Be aware not to apply force even after mounting.

2-2 Soldering

- 1) To leave a semiconductor device at high temperature for many hours is undesirable, and also, soldering should be conducted at low temperature in a short time whichever you use a solder iron, reflow method.
- 2) The standard of solder heat resistance test for discrete devices is at 260 °C for 10 seconds and at 350 °C for 3 seconds.
- 3) We conduct solderability test with flux at 230 °C for 5 seconds.
When you use high acid or alkaline flux, it might cause lead corrosion or peculiar influence.
Please note the usage.
- 4) When a printed circuit board has warpage by soldering, please note that a semiconductor device has stress.
- 5) The condition for a soldering iron and solder tub is no electric leakage. Especially for FET type transistors and high frequency devices, consideration such as earthing of soldering instruments is required.

2-3 Cleaning (Flux cleaning)

- 1) Flux residue can cause corrosion, insulation deterioration, etc., and can cause electronic circuit problems.
Please do the cleaning.
(Recommend chlorine-free rosin flux)
- 2) Be careful when using ultrasonic cleaning, as it may affect the product depending on the frequency, ultrasonic output, cleaning time, substrate shape, etc.

2-4 About using chemicals

This product is a precision part.
In case of using solvent, Please confirm beforehand that there is no problem with the product.



Ultra small surface mounting type

3. Precautions for using

3-1 Storage condition and term

Expiration date for device storage is for two years from the date shown in the packing label at temperature (5 °C - 35 °C) and relative humidity (45 % - 75 %).

Please be careful not to pass this period.

As for an expired device, please confirm the solderab

3-2 Transportation

During transportation, please do not expose devices to excessive mechanical vibration and shock, and also prevent them from being wet with water.

3-3 Measurement

When you inspect characteristics of devices, please give attention to surge voltage prevention from measuring instruments, wrong connections and short circuits between terminals.

Also, an inspection over product ratings should not be conducted.

As for hig

3-4 Maximum ratings

- 1) In general, maximum ratings are regulated as the absolute maximum ratings, and they are device limit values which shall be never exceeded in any condition at any time. By exceeding the rating a device will be deteriorated or destroyed and its characterist
- 2) Applied voltage, current, reverse voltage, dissipation power, junction temperature, and storage temperature etc., have their maximum ratings.
Please refer to product specifications for the ratings.

Request for your special attention and precautions in using the technical information and semiconductors described in this book

- (1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.
- (2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products. No license is granted in and to any intellectual property right or other right owned by Panasonic Corporation, Nuvoton Technology Corporation Japan or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information de-scribed in this book.
- (3) The products described in this book are intended to be used for general applications (such as office equipment, communications equipment, measuring instruments and household appliances), or for specific applications as expressly stated in this book.
Please consult with our sales staff in advance for information on the following applications, moreover please exchange documents separately on terms of use etc.: Special applications (such as for in-vehicle equipment, airplanes, aerospace, automotive equipment, traffic signaling equipment, combustion equipment, medical equipment and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
Unless exchanging documents on terms of use etc. in advance, it is to be understood that our company shall not be held responsible for any damage incurred as a result of or in connection with your using the products described in this book for any special application.
- (4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. We do not guarantee quality for disassembled products or the product re-mounted after removing from the mounting board.
When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.
- (7) When reselling products described in this book to other companies without our permission and receiving any claim of request from the resale destination, please understand that customers will bear the burden.
- (8) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of our company.